

ANA-QUICK® NYLON SERIES

PA6 CONDUIT - EXTRA FLEXIBLE



DESCRIPTION:

For insulation, mechanical protection and environmental preservation of cables in the electrical installation of machinery, industrial equipment and telecommunications.



AC6L conduits are corrugated polyamide conduits specially designed for machine tool applications that require protection for cables. AC6L is a standard wall conduit, which is UL Recognized.

SPECIFICATIONS:

- Made of specially modified polyamide (PA6)
- Special patented profile for housing the O-Ring sealing to provide a higher IP protection
- Free of halogen, phosphorous and cadmium
- Self-extinguishing (HB according to UL94)
- Temp. range: -40°C to +105°C (150°C short term)
- UV resistant
- Colour: black


APPLICATIONS:

- Machine building, switch cabinets, movable machinery, rail vehicles, commercial vehicles, construction machinery.

CONDUIT: AC6L - LIGHT WALL



Size NW	Item ID	Diameter mm (inches)		Bend Radius mm (inches)	Package m
		Inside	Outside		
7 (1/4")	AC6L-07B	6.3 (0.248)	10.0 (0.394)	15 (1.2)	50
10 (5/16")	AC6L-10B	9.7 (0.382)	13.0 (0.512)	20 (11.8)	50
12 (3/8")	AC6L-12B	12.2 (0.480)	15.8 (0.622)	30 (1.2)	50
17 (1/2")	AC6L-17B	16.8 (0.661)	21.2 (0.835)	40 (5.9)	50
23 (3/4")	AC6L-23B	22.6 (0.890)	28.5 (1.122)	55 (11.8)	50
29 (1")	AC6L-29B	28.3 (1.114)	34.5 (1.358)	65 (1.2)	50
36 (1-1/4")	AC6L-36B	36.3 (1.429)	42.5 (1.673)	80 (5.9)	30
48 (1-1/2")	AC6L-48B	47.4 (1.866)	54.5 (2.146)	95 (0.6)	30



FITTINGS FINDER



PAGE 75-80