



## Aluminum Flex Type CSA: Non-Jacketed Flexible Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight (Kg) Per Meter
				Min	Max		
5/16" (10)	30030	75	7.92 (0.312)	n/a	13.00 (0.512)	89 (3.5)	0.088
	30032	300					
3/8" (12)	30040	75	9.53 (0.375)	14.22 (0.560)	15.49 (0.610)	102 (4.0)	0.099
	30042	300					
7/16" (14)	30050	75	11.1 (0.437)	n/a	17.15 (0.675)	114 (4.5)	0.105
	30052	300					
1/2" (16)	30060	30	15.87 (0.625)	21.84 (0.860)	23.37 (0.920)	152 (6.0)	0.245
	30066	300					
3/4" (21)	30070	30	20.62 (0.812)	26.54 (1.045)	28.97 (1.105)	203 (8.0)	0.313
	30072	150					
	30073	300					
1" (27)	30080	30	25.39 (1.000)	33.02 (1.300)	35.05 (1.380)	254 (10.0)	0.481
	30081	150					
1-1/4" (35)	30090	15	31.75 (1.250)	39.37 (1.550)	41.40 (1.630)	318 (12.5)	0.578
	30092	75					
1-1/2" (41)	30100	15	38.10 (1.500)	46.99 (1.850)	49.53 (1.950)	381 (15.0)	0.660
	30102	45					
2" (53)	30110	15	50.79 (2.000)	59.69 (2.350)	62.23 (2.450)	508 (20.0)	0.876
	30111	30					
2-1/2" (63)	30120	15	63.50 (2.500)	72.64 (2.860)	77.72 (3.060)	635 (25.0)	1.180
3" (78)	30130	15	76.20 (3.000)	90.42 (3.360)	90.42 (3.560)	762 (30.0)	1.265
3-1/2" (91)	30140	15	88.90 (3.500)	98.04 (3.860)	103.12 (4.060)	889 (35.0)	1.465
4" (103)	30150	15	101.60 (4.000)	110.74 (4.360)	115.82 (4.560)	1016 (40.0)	1.693

All dimensions in mm (inches)



**Modified S Profile**  
3/8" thru 4"

### Aluminum Flex Type CSA:



- Non-jacketed aluminum flexible conduit
- Designed for commercial and industrial applications in Canadian market.
- Uses standard 'L-16' series connectors.
- Available in custom cut lengths

For cutting instructions, see page 32  
For Chemical Resistance, see page 33

#### SPECIFICATIONS:

- Aluminum strip-wound core
- Temperature range:  
+500°C Maximum
- CSA Approved: # 17419

#### APPLICATIONS:

- Commercial and industrial applications where liquid-tight protection is not required.

Anamet Canada Inc.  
PO Box 550  
Colborne, Ontario K0K 1S0

Phone: (905) 355-2122  
Fax: (905) 355-3110  
www.anametcanada.com  
E-mail: csr@anametcanada.com