



Steel Flex Type DSL: Non-Jacketed Extra Flexible Steel Conduit

Actual ID	Description	Item	Std. Pkg.	Inside Diameter	Outside Diameter	Bend Diameter	Weight (Kg)
Size	ID	ID	METERS	Min	Max	mm (in.)	Per Meter
3/16"	DSL-3	460012	76	4.78 (0.188)	6.98 (0.275)	51 (2.0)	0.067
1/4"	DSL-4	460022	76	6.35 (0.250)	8.89 (0.350)	51 (2.0)	0.092
5/16"	DSL-5	460032	76	7.95 (0.313)	10.97 (0.432)	63 (2.5)	0.105
		460032-3	914				
3/8"	DSL-6	460042	61	9.53 (0.375)	12.65 (0.498)	76 (3.0)	0.148
		460042-2	610				
7/16"	DSL-7	460052	61	11.13 (0.438)	14.35 (0.565)	76 (3.0)	0.164
1/2"	DSL-8	460057	61	12.70 (0.500)	16.08 (0.633)	76 (3.0)	0.180
9/16"	DSL-9	460067	61	14.30 (0.563)	17.78 (0.700)	76 (3.0)	0.213
5/8"	DSL-10	460072	45	15.87 (0.625)	19.38 (0.763)	102 (4.0)	0.289
3/4"	DSL-12	460077	45	19.05 (0.750)	22.73 (0.895)	102 (4.0)	0.356

All dimensions in mm (inches)



Square Lock Design

SPECIFICATIONS:

- Galvanized steel square-lock non-jacketed conduit
- Zinc coated steel provides superior corrosion resistance
- Temperature range: +450°C Maximum
- Exceptional flexibility for tight "U" bend radius

APPLICATIONS:

- OEM applications where tight bend radius is required, but no approvals are required.

Type DSL Galvanized Steel Conduit:

RoHS

- Ultra flexible galvanized steel conduit
- Designed for OEM applications where high flexibility but no approvals are required.
- Installs easily using standard armoured or flexible conduit connectors.
- Available in custom cut lengths