



## Firetech: Protective Sleeving

### Firetech Sleeve/Wrap/Tape/Blanket:

- Flexible Sleeving for protection of cables from high heat or flame.
- Silicone based cover over a knitted glass fiber sleeve.
- Superior temperature range for extreme environments.
- Abrasion resistant—Ready for the worst environment.
- The ultimate protection for harsh industrial applications.
- Can be enhanced by adding additional layer of Firetech Lite.



### Firetech VCO:

- Any of the standard Firetech Sleeves can be slit and sewn with a high temperature hook-and-loop closure. This allows easy assembly and removal without disconnecting cables.
- Ordered by required length. Consult Factory for details.



### Firetech Lite:

- Flexible Sleeving for protection of cables from high heat.
- Braided glass fiber sleeve.
- Superior temperature range for extreme environments.
- Can be used to increase heat resistance of Firetech Sleeve.



### Firetech Connectors:

- Anamet Stainless Steel fittings for Firetech come with a special internal collar to allow the Firetech Sleeve to be held firmly, creating a method of sealing the ends of the sleeve.





## Firetech SLEEVE



The following part numbers are available in non-standard lengths as required:

FTS-4 (1/4")  
 FTS-6 (3/8")  
 FTS-8 (1/2")  
 FTS-12 (3/4")  
 FTS-16 (1")

Change part number to:  
 FTS-x-9

Description	Inside Diameter Inches	Weight (kg) per package	Std. Pkg. FOOT
FTS-4-5	1/4"	1.6	50
FTS-5-5	5/16"	1.8	50
FTS-6-5	3/8"	2.25	50
FTS-7-5	7/16"	2.5	50
FTS-8-5	1/2"	2.95	50
FTS-10-5	5/8"	3.2	50
FTS-12-5	3/4"	3.85	50
FTS-14-5	7/8"	4.1	50
FTS-16-5	1"	4.75	50
FTS-18-5	1-1/8"	5	50
FTS-20-5	1-1/4"	5.9	50
FTS-22-5	1-3/8"	6.8	50
FTS-24-5	1-1/2"	7.75	50
FTS-26-5	1-5/8"	7.95	50
FTS-28-5	1-3/4"	8.2	50
FTS-32-5	2"	9.1	50
FTS-36-5	2-1/4"	9.75	50
FTS-40-5	2-1/2"	10.45	50
FTS-44-5	2-3/4"	11.6	50
FTS-48-5	3"	13.2	50
FTS-52-5	3-1/4"	15.7	50
FTS-56-5	3-1/2"	16.35	50
FTS-60-5	3-3/4"	16.8	50
FTS-64-5	4"	17.5	50

## SPECIFICATIONS:

- Knitted glass fiber coated with silicone rubber (non-asbestos)
- Colour: Red
- Temperature range:  
 +260°C (500°F) Continuous  
 +1090°C (2000°F) 15-20 min.  
 +1650°C (3000°F) 15-30 sec.
- Silicone cover sheds molten metal/glass immediately avoiding heat transfer

## APPLICATIONS:

- Extreme duty applications
- Extreme high heat or flame

## Firetech WRAP



Description	Width Inches	Weight (kg) per package	Std. Pkg. FEET
FTW-1-5	1"	1.35	50
FTW-2-5	2"	2.25	50
FTW-3-5	3"	3.65	50
FTW-4-5	4"	4.75	50
FTW-5-5	5"	5.9	50

## TAPE



Description	W x L x Thickness Inches	Weight (kg) per roll	Std. Pkg.
FTT-16	1" x 432" x .020"	0.14	Per Roll
FTT-24	1 1/2" x 432" x .060"	0.45	Per Roll

## BLANKET



Description	Width & Sides Coated	Weight (kg) per foot	Std. Pkg.
FSH-36-2	36" FSH-36-2 coated 2 sides	0.36	Per Foot
FSH-60-2	60" FSH-60-2 coated 2 sides	0.91	Per Foot
FSH-40-1	40" FSH-40-1 coated 1 side	0.6	Per Foot

Phone: (905) 355-2122  
 Fax: (905) 355-3110  
 www.anametcanada.com  
 E-mail: csr@anametcanada.com

Anamet Canada Inc.  
 PO Box 550  
 Colborne, Ontario K0K 1S0



## Firetech Lite: Extreme Temperature Sleeve

### Firetech Lite:



Description	Inside Diameter	Weight (kg)	Std. Pkg.
	Inches	per package	FOOT
FTL-8-5	1/2"	2.95	330
FTL-12-5	3/4"	3.85	300
FTL-16-5	1"	4.75	290
FTL-20-5	1-1/4"	5.9	280
FTL-24-5	1-1/2"	7.75	225
FTL-32-5	2"	9.1	190
FTL-40-5	2-1/2"	10.45	180
FTL-48-5	3"	13.2	170
FTL-64-5	4"	17.5	140

### SPECIFICATIONS:

- Braided glass fibre sleeve
- Colour: White
- Temperature range:  
+538°C (1000°F) Continuous  
+705°C (1300°F) 15-20 min.
- Provides economical cable protection where exposure to molten splash, oils or moisture is not a factor.
- Can be used in conjunction with Firetech Sleeve to provide additional insulation values.

### APPLICATIONS:

- High heat areas where splash and oils are not a factor.

## SSFT Series Liquid-tight Connectors:

### Straight:



FTS/FTL Size	Item ID	Dimensions			KO Size	Weight Kg/Pkg	Standard Package
		A	B	C			
1/2"	SSFT38	37.00 (1.457)	13.00 (0.512)	26.00 (1.024)	1/2"	1.6	25
5/8"	SSFT50	37.00 (1.457)	13.00 (0.512)	29.00 (1.142)	1/2"	2.0	25
7/8"	SSFT75	40.00 (1.575)	15.00 (0.591)	35.00 (1.379)	3/4"	1.1	10
1"	SSFT100	46.00 (1.811)	15.00 (0.591)	45.00 (1.772)	1"	0.7	5

All dimensions in mm (inches)

### 90 Degree:



FTS/FTL Size	Item ID	Dimensions				KO Size	Weight Kg/Pkg	Standard Package
		A	B	C	D			
1/2"	SSFT9038	36.00 (1.417)	13.00 (0.512)	26.00 (1.024)	43.00 (1.693)	1/2"	1.0	10
5/8"	SSFT9050	36.00 (1.417)	13.00 (0.512)	29.00 (1.142)	43.00 (1.693)	1/2"	1.3	10
7/8"	SSFT9075	43.00 (1.693)	15.00 (0.591)	35.00 (1.379)	48.00 (1.890)	3/4"	1.6	10
1"	SSFT90100	48.00 (1.890)	15.00 (0.591)	45.00 (1.772)	59.00 (2.323)	1"	1.2	5

All dimensions in mm (inches)