



Aluminum Flex Type RWA: Non-Jacketed Flexible Conduit



Trade Size	Item ID	Std. Pkg. FEET	Inside Diameter Min	Outside Diameter Min / Max		Bend Diameter	Weight (Kg) Per 100 Feet
3/8" (12)	441503	100	9.53 (0.375)	14.22 (0.560)	15.49 (0.610)	102 (4.0)	3.0
	441504	1000					
1/2" (16)	441513	100	15.87 (0.625)	21.84 (0.860)	23.37 (0.920)	152 (6.0)	4.9
	441517	1000					
3/4" (21)	441523	100	20.62 (0.812)	26.54 (1.045)	28.97 (1.105)	203 (8.0)	6.4
	441526	500					
	441527	1000					
1" (27)	441532	50	25.39 (1.000)	33.02 (1.300)	35.05 (1.380)	254 (10.0)	10.0
	441533	300					
	441534	500					
1-1/4" (35)	441542	50	31.75 (1.250)	39.37 (1.550)	41.40 (1.630)	318 (12.5)	19.0
1-1/2" (41)	441551	25	38.10 (1.500)	46.99 (1.850)	49.53 (1.950)	381 (15.0)	21.0
2" (53)	441561	25	50.79 (2.000)	59.69 (2.350)	62.23 (2.450)	508 (20.0)	28.0

All dimensions in mm (inches)

Modified S Profile
3/8" thru 4"



SPECIFICATIONS:

- Aluminum strip-wound core, non-jacketed
- Temperature range: +500°C Maximum
- UL Approved: # E98045
- 3/8" only is CSA and UL Approved

APPLICATIONS:

- Commercial and industrial applications where liquid-tight is not required and UL approval is needed.

Aluminum Flex Type RWA:



- Non-jacketed aluminum flexible conduit
- Designed for commercial and industrial applications in US market.
- Uses standard 'L-16' series connectors.
- Available in custom cut lengths.

For cutting instructions, see page 32
For Chemical Resistance, see page 33