



## Conseal Type CSA: Standard Flexible Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight (Kg) Per Meter
				Min	Max		
3/8" (12)	10041	30	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	102 (4.0)	0.35
	10044	300					
1/2" (16)	10061	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)	0.42
	10063	150					
	10064	300					
3/4" (21)	10071	30	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	203 (8.0)	0.55
	10073	150					
	10074	300					
1" (27)	10081	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)	0.80
	10083	150					
1-1/4" (35)	10090	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)	1.13
	10091	75					
1-1/2" (41)	10100	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)	1.45
	10101	45					
2" (53)	10111	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)	1.67
	10113	30					
2-1/2" (63)	34075	8	62.99 (2.480)	72.10 (2.840)	73.00 (2.875)	635 (25.0)	2.88
3" (78)	34085	8	77.98 (3.070)	87.90 (3.460)	88.90 (3.500)	762 (30.0)	4.00
4" (103)	34095	8	101.60 (4.000)	113.30 (4.460)	114.30 (4.500)	1016 (40.0)	6.00

All dimensions in mm (inches)



**Modified S Profile** with cord packing 3/8" thru 3/4"

**Square Lock Profile** with cord packing 1" thru 2"

**Interlocked Profile** 2-1/2" thru 4"

### Conseal Type CSA:



- Flexible metal core liquid-tight conduit.
- Suitable for use in hazardous locations per CEC: Class I, Zone 2 & Div. 2; Class II Div. 1 & 2; Class III Div. 1 & 2.
- Also available by special order in other colours. (consult factory)
- Sequentially meter marked for easy cutting and stock control.
- Uses standard liquid-tight connectors for easy installation.
- Available in custom cut lengths

For connectors for this conduit, see page 18-19  
 For cutting instructions, see page 33  
 For Chemical Resistance, see page 34

#### SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Black
- Temperature range: -20°C to +75°C
- FT-4 Rated
- UV (sunlight) Resistant
- Corrosion Resistant
- Sequentially meter marked
- CSA Approved # 20817

#### APPLICATIONS:

- Standard industrial and commercial applications
- Motor hookup