



Conseal Type HTC: High Temperature Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter		Outside Diameter		Bend Diameter	Weight (Kg) Per Meter
			Min	Max	Min	Max		
3/8" (12)	14041	30	12.29 (0.484)	17.5 (0.690)	18.00 (0.710)	102 (4.0)	0.33	
1/2" (16)	14061	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)	0.40	
3/4" (21)	14071	30	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	203 (8.0)	0.53	
1" (27)	14081	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)	0.73	
1-1/4" (35)	14090	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)	1.07	
1-1/2" (41)	14100	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)	1.33	
2" (53)	14112	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)	1.67	

All dimensions in mm (inches)



Modified S Profile with cord packing 3/8" thru 3/4"



Square Lock Profile with cord packing 1" thru 2"

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Black
- Temperature range: -20°C to +105°C
- UV (sunlight) Resistant
- Corrosion Resistant
- Sequentially meter marked

APPLICATIONS:

- Applications for high temperature.
- Steel and Petrochemical industries
- Applications where no approvals are required.

Conseal Type HTC:

RoHS

- Flexible metal core liquid-tight conduit
- Designed for applications where high temperature is required, but no approvals are needed.
- Also available by special order in other colours. (consult factory)
- Sequentially meter marked for easy cutting and stock control.
- Uses standard liquid-tight connectors for easy installation.
- Available in custom cut lengths

For connectors for this conduit, see page 18-19
 For cutting instructions, see page 33
 For Chemical Resistance, see page 34