



## Sealtite Type HTC: CSA High Temperature Flexible Conduit

Trade	Item	Std. Pkg.	Inside Diameter	Outside Diameter		Bend	Weight
Size	ID	METERS	Min	Min	Max	Diameter	Kg/m (lbs/cft)
3/8" (12)	14041	30	12.29 (0.484)	17.5 (0.690)	18.00 (0.710)	102 (4.0)	0.33 (22)
1/2" (16)	14061	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)	0.40 (27)
	14062	150					
	14063	300					
3/4" (21)	14071	30	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	203 (8.0)	0.53 (36)
	14072	150					
	14072	300					
1" (27)	14081	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)	0.73 (49)
	14083	150					
1-1/4" (35)	14090	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)	1.07 (72)
1-1/2" (41)	14100	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)	1.33 (89)
2" (53)	14112	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)	1.67 (112)

All dimensions in mm (inches)



Modified S Profile with cord packing 3/8" thru 1"

Square Lock Profile with cord packing 1-1/4" thru 2"

### Sealtite Type HTC:



- Flexible metal core liquid-tight conduit
- Designed for applications where high temperature is required,
- Also available by special order in other colours. (consult factory)
- Sequentially meter marked for easy cutting and stock control.
- Uses standard liquid-tight connectors for easy installation.
- Available in custom cut lengths

For connectors for this conduit, see page 19-20  
 For cutting instructions, see page 37  
 For Chemical Resistance, see page 38

#### SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Black
- Temp. range: -20°C to +105°C (-4°F to +221°F)
- UV (sunlight) Resistant
- Corrosion Resistant
- Sequentially meter marked
- CSA Approved # 20817

#### APPLICATIONS:

- Applications for high temperature.
- Steel and Petrochemical industries
- Applications where CSA approval is required.