



Conseal Type HTX: Extra High Temperature Flexible Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight (Kg) Per Meter
				Min	Max		
3/8" (12)	13041	30	12.29 (0.484)	17.5 (0.690)	18.00 (0.710)	102 (4.0)	0.35
1/2" (16)	13061	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)	0.42
3/4" (21)	13071	30	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	203 (8.0)	0.55
1" (27)	13081	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)	0.80
1-1/4" (35)	13090	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)	1.13
1-1/2" (41)	13100	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)	1.45
2" (53)	13110	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)	1.67

All dimensions in mm (inches)



Modified S Profile with cord packing 3/8" thru 3/4"

Square Lock Profile with cord packing 1" thru 2"

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight TPE jacket
- Colour: Yellow
- Temperature range: -60°C to +135°C Intermittent to 150°C
- UV (sunlight) Resistant
- Extra Corrosion Resistant
- Oil Resistant

APPLICATIONS:

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where no approvals are required

Conseal Type HTX:

- Flexible metal core liquid-tight conduit
- Designed for extreme temperatures. (-60°C to +135°C)
- Available standard in Yellow.
- Also available by special order in other colours. (consult factory)
- Sequentially meter marked for easy cutting and stock control.
- Uses standard liquid-tight connectors for easy installation.
- Available in custom cut lengths

For connectors for this conduit, see page 18-19
For cutting instructions, see page 34