

Type EFL

Flexible, Light Weight, Liquid-Tight, Aluminum Core, PVC Covered Conduit



Square Locked Design with cord packing 5/16" - 1-1/4".



Interlocked Design 1-1/2" and up.

UPC	Trade Size	Standard Length Meters / Feet	Min. Inside Bend Diameter (inches)
622620 38002 9	3/8	30 / 100	4
622620 38012 8	1/2	30 / 100	5
622620 38022 7	3/4	30 / 100	6
622620 38031 9	1	30 / 100	8
622620 38041 8	1-1/4	15 / 50	9
622620 38051 7	1-1/2	15 / 50	11
622620 38061 6	2	15 / 50	14
622620 38071 5	2-1/2	15 / 50	19
622620 38081 4	3	7.6 / 25	30
622620 38091 3	4	7.6 / 25	34

Standard colour - grey.

Sealtite® Type EFL additional information

- Constructed of continuous lightweight aluminum strip inner core with cord packing in sizes from 3/8" to 1-1/4" for extra flexibility.
- Constructed continuous interlocked lightweight aluminum strip inner core on sizes over 1-1/4".
- Uses standard readily available liquid-tight connectors.
- Smooth PVC cover for exposed applications. Sunlight resistant.
- Rated from -20° C to + 60° C.