

Type EFST

Flexible, All Purpose, Liquid-Tight, Zinc Coated Steel Core, PVC Covered Conduit



Square Locked Design with cord packing 5/16" - 1-1/4".



Interlocked Design 1-1/2" and up.

UPC	Trade Size	Standard Length Meters / Feet	Min. Inside Bend Diameter (inches)
622620 35983 4	1/4	30 / 100	3.5
622620 35981 0	1/4	152 / 500	3.5
622620 35993 3	5/16	30 / 100	4
622620 35991 9	5/16	152 / 500	4
622620 36202 5	3/8	30 / 100	4
622620 36212 4	1/2	30 / 100	5
622620 36222 3	3/4	30 / 100	6
622620 36231 5	1	30 / 100	8
622620 36241 4	1-1/4	15 / 50	9
622620 36251 3	1-1/2	15 / 50	11
622620 36261 2	2	15 / 50	14

Consult factory for information on larger sizes

Standard colour 1/4" & 5/16" - black. Standard colour 3/8" & up - grey.

Sealtite® Type EFST additional information

- Constructed of continuous square locked zinc coated steel strip inner core with cord packing in sizes from 1/4" to 1-1/4" for extra flexibility.
- Constructed continuous interlocked zinc coated steel strip inner core on sizes over 1-1/4".
- Uses standard readily available liquid-tight connectors.
- Smooth PVC cover for exposed applications.
- Rated from -20° C to + 60° C.