



Sealtite Type CNP: Non-metallic Robotic Flexible Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter Min Max		Bend Diameter	Weight (Kg) Per Meter
3/8" (12)	38602	30	12.32 (0.485)	19.20 (0.755)	19.68 (0.775)	127 (5.0)	0.24
	38601	76					
1/2" (16)	38612	30	15.75 (0.620)	23.11 (0.910)	23.62 (0.930)	152 (6.0)	0.33
	38611	61					
	38613	243					
3/4" (21)	38622	30	20.70 (0.815)	29.21 (1.150)	29.72 (1.170)	203 (8.0)	0.46
	38621	53					
	38623	243					
1" (27)	38631	30	26.16 (1.030)	35.94 (1.415)	36.57 (1.440)	305 (12.0)	0.66
	38633	152					
1-1/4" (35)	38641	15	34.79 (1.370)	45.72 (1.800)	46.35 (1.825)	356 (14.0)	0.92
	38643	61					
1-1/2" (41)	38651	15	40.26 (1.585)	51.94 (2.045)	52.83 (2.080)	406 (16.0)	1.27
	38653	30					
2" (53)	38661	15	51.94 (2.045)	66.17 (2.605)	67.06 (2.640)	457 (18.0)	1.87
	38663	30					

All dimensions in mm (inches)



Nylon Reinforced with inner and outer PVC jackets

Sealtite Type CNP:

RoHS



- Non-metallic Type A liquid-tight conduit
- Great for constantly flexing applications
- Good for abrasion and where physical abuse may exist
- Available standard in Orange.
- Also available in Grey by special order.

SPECIFICATIONS:

- Smooth inner PVC core with outer oil resistant PVC cover bonded together with nylon reinforcing braid
- Colour: Orange
- Temperature range: -20°C to +75°C
- UV (sunlight) Resistant
- Oil Resistant
- CSA Approved: # LL15275-10
- UL Approved: # E75863

APPLICATIONS:

- Automotive applications requiring continuous flexing
- Food machine applications where non-metallic and flexing required

For connectors for this conduit, see page 21
 For cutting instructions, see page 33
 For Chemical Resistance, see page 34

Anamet Canada Inc.
 PO Box 550
 Colborne, Ontario K0K 1S0


Phone: (905) 355-2122
 Fax: (905) 355-3110
www.anametcanada.com
 E-mail: csr@anametcanada.com



Connectors Type STNM / SSNM: Connectors for CNP Conduit (ONLY)




Straight:



Trade	Item	Dimensions			KO Size	Weight	Standard
Size	ID	A	B	C		Kg/Pkg	Package
3/8"	STNM38	54.76 (2.156)	15.09 (0.594)	29.36 (1.156)	1/2"	1.0	25
1/2"	STNM50	65.89 (2.594)	15.09 (0.594)	33.35 (1.313)	1/2"	1.3	25
3/4"	STNM75	65.89 (2.594)	15.09 (0.594)	41.27 (1.625)	3/4"	1.6	25
1"	STNM100	73.02 (2.875)	18.26 (0.719)	49.23 (1.938)	1"	1.2	5
1-1/4"	STNM125	86.51 (3.406)	19.05 (0.750)	61.11 (2.406)	1-1/4"	0.8	5
1-1/2"	STNM150	87.33 (3.438)	19.05 (0.750)	70.64 (2.781)	1-1/2"	1.1	2
2"	STNM200	100.81 (3.969)	19.05 (0.750)	85.73 (3.375)	2"	1.5	1

All dimensions in mm (inches)

90 Degree:



Trade	Item	Dimensions mm (in.)				KO Size	Weight	Std.
Size	ID	A	B	C	D		Kg/Pkg	Pkg.
3/8"	STNM9038	51.59 (2.031)	15.09 (0.594)	29.36 (1.156)	31.75 (1.250)	1/2"	1.0	25
1/2"	STNM9050	60.32 (2.375)	15.09 (0.594)	33.35 (1.313)	32.54 (1.281)	1/2"	1.3	25
3/4"	STNM9075	63.50 (2.500)	15.09 (0.594)	41.27 (1.625)	36.53 (1.438)	3/4"	1.6	10
1"	STNM90100	69.85 (2.750)	18.26 (0.719)	49.23 (1.938)	44.45 (1.750)	1"	1.2	5
1-1/4"	STNM90125	88.11 (3.469)	19.05 (0.750)	61.11 (2.406)	50.01 (1.969)	1-1/4"	0.8	5
1-1/2"	STNM90150	91.29 (3.594)	19.05 (0.750)	70.64 (2.781)	57.15 (2.250)	1-1/2"	1.1	2
2"	STNM90200	122.25 (4.813)	19.05 (0.750)	85.73 (3.375)	64.29 (2.531)	2"	1.5	1

All dimensions in mm (inches)

STNM Series Liquid-tight Connectors:




- Only approved for use with Sealtite Type CNP flexible conduit.

SPECIFICATIONS:

- Zinc plated Steel
- Colour: Silver
- CSA Approved.
- UL Approved.

Stainless Steel Connectors Straight:



Trade	Item	Dimensions			KO Size	Weight	Standard
Size	ID	A	B	C		Kg/Pkg	Package
3/8"	SSNM38	62.00 (2.441)	15.00 (0.591)	32.00 (1.260)	1/2"	1.0	10
1/2"	SSNM50	68.00 (2.677)	15.00 (0.591)	36.00 (1.417)	1/2"	1.3	10
3/4"	SSNM75	68.00 (2.677)	15.00 (0.591)	41.00 (1.614)	3/4"	1.6	10
1"	SSNM100	77.00 (3.031)	18.00 (0.709)	50.00 (1.969)	1"	1.2	5

All dimensions in mm (inches)

SPECIFICATIONS:

- 303 Stainless Steel