



Sealtite Type EFST: Extra Flexible Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight (Kg) Per Meter
				Min	Max		
1/4"	35983	30	6.22 (0.245)	11.30 (0.445)	11.68 (0.460)	89 (3.5)	0.21
	35981	152					
5/16" (10)	35993	30	9.91 (0.390)	14.22 (0.560)	14.61 (0.575)	102 (4.0)	0.22
	35991	152					
3/8" (12)	36202	30	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	102 (4.0)	0.35
1/2" (16)	36212	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)	0.42
3/4" (21)	36222	30	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	203 (8.0)	0.55
1" (27)	36231	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)	0.80
1-1/4" (35)	36241	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)	1.13
1-1/2" (41)	36251	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)	1.45
2" (53)	36261	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)	1.67

All dimensions in mm (inches)



Square Lock Profile with cord packing 1/4" thru 1-1/4"



Interlocked Profile 1-1/2" thru 2"

Sealtite Type EFST:

RoHS

- Flexible metal core liquid-tight conduit
- Designed for applications where no approvals are required.
- Also available in Black by special order.
- Uses standard liquid-tight connectors for easy installation.
- Available in custom cut lengths

For connectors for this conduit, see page 18-19
 For cutting instructions, see page 33
 For Chemical Resistance, see page 34

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Grey (1/4" and 5/16" standard colour Black)
- Temperature range: -20°C to +60°C
- UV (sunlight) Resistant
- Corrosion Resistant

APPLICATIONS:

- Applications where very small ID liquid-tight is required (ie: 1/4")
- Applications where no approvals are required.