

Sealtite Type HCX: Extreme Temperature Flexible Conduit



Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight (Kg) Per Meter
				Min	Max		
3/8" (12)	39102	30	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	102 (4.0)	0.33
1/2" (16)	39112	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	127 (5.0)	0.40
3/4" (21)	39122	30	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	153 (6.0)	0.64
1" (27)	39131	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	203 (8.0)	0.83
1-1/4" (35)	39141	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	229 (9.0)	1.00
1-1/2" (41)	39151	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	279 (11.0)	1.60
2" (53)	39161	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	356 (14.0)	2.07

All dimensions in mm (inches)

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight TPE jacket
- Colour: Black
- Temperature range: -60°C to +150°C
- UV (sunlight) Resistant
- Extra Corrosion Resistant
- Oil Resistant

APPLICATIONS:

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where no approvals are required

Square Lock Design with cord packing 1/4" thru 1-1/4"



Interlocked Design 1-1/2" thru 2"



Sealtite Type HCX:

RoHS

- Flexible metal core liquid-tight conduit
- Designed for extreme temperature applications where superior resistance to temperature ranges is required. (-60°C to +150°C)
- Available standard in Black.
- Uses standard liquid-tight connectors for easy installation.

For connectors for this conduit, see page 18-19
For cutting instructions, see page 34