



Sealtite Type MTC: Machine Tool Extra Flexible Conduit

Trade	Item	Std. Pkg.	Inside Diameter	Outside Diameter		Bend	Weight (Kg)
Size	ID	METERS	Min	Min	Max	Diameter	Per Meter
3/8" (12)	38302	30	12.29 (0.484)	17.25 (0.679)	17.88 (0.704)	76 (3.0)	0.24
	38304	244					
1/2" (16)	38312	30	15.80 (0.622)	20.78 (0.818)	21.41 (0.843)	102 (4.0)	0.30
	38314	152					
3/4" (21)	38322	30	20.83 (0.820)	25.63 (1.009)	26.26 (1.034)	127 (5.0)	0.36
	39328	152					
1" (27)	38331	30	26.44 (1.041)	31.19 (1.228)	31.95 (1.258)	152 (6.0)	0.45
	38338	122					
1-1/4" (35)	38341	15	35.05 (1.380)	39.75 (1.565)	40.51 (1.595)	178 (7.0)	0.60
	38348	76					
1-1/2" (41)	38351	15	40.01 (1.575)	46.48 (1.830)	47.24 (1.860)	203 (8.0)	1.04
	38354	46					
2" (53)	38361	15	51.31 (2.020)	57.66 (2.270)	58.42 (2.300)	254 (10.0)	1.30
	38638	30					

All dimensions in mm (inches)



Angled Profile 3/8" thru 2"

Sealtite Type MTC:

RoHS

- Flexible metal core liquid-tight conduit.
- Designed for Machine Tool industry for high flexibility.
- Very tight bend radius makes wiring machine tools easier.
- Uses standard liquid-tight connectors for easy installation.

For connectors for this conduit, see page 18-19
 For cutting instructions, see page 33
 For Chemical Resistance, see page 34

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Black
- Temperature range: -20°C to +60°C
- UV (sunlight) Resistant
- Corrosion Resistant
- Tight bend radius

APPLICATIONS:

- High flexibility
- Machine Tool industry