



Sealtite Type OR: Oil-Resistant Flexible Conduit

Trade Size	Item ID	Std. Pkg. METERS	Inside Diameter Min	Outside Diameter		Bend Diameter	Weight (Kg) Per Meter
				Min	Max		
3/8" (12)	36602	30	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	102 (4.0)	0.33
1/2" (16)	36612	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	127 (5.0)	0.36
3/4" (21)	36622	30	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	153 (6.0)	0.60
1" (27)	36631	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	203 (8.0)	0.77
1-1/4" (35)	36641	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	229 (9.0)	1.00
1-1/2" (41)	36651	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	279 (11.0)	1.57
2" (53)	36661	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	356 (14.0)	2.07

All dimensions in mm (inches)



Square Lock Design with
cord packing 3/8" thru 1-1/4"



Interlocked Design 1-1/2"
thru 2"

Sealtite Type OR:

RoHS

- Flexible metal core liquid-tight conduit.
- Designed for applications that need superior resistance to petroleum, synthetic oils and chemical degradation.
- Also available in Black by special order.
- Uses standard liquid-tight connectors for easy installation.

For connectors for this conduit, see page 18-19
For cutting instructions, see page 32
For Chemical Resistance, see page 33

SPECIFICATIONS:

- Galvanized steel core with Liquid-tight PVC jacket
- Colour: Black
- Temperature range: -23°C to +105°C
- UV (sunlight) Resistant
- Extra Oil Resistant
- Corrosion Resistant

APPLICATIONS:

- Extreme resistance to oil.
- Petrochemical and steel industries
- Applications where no approvals are required.