

Type UA-CSA

Flexible, Heavy Duty, Liquid-Tight, Zinc Coated Steel Core, PVC Covered Conduit, UL & CSA Approved



Square Locked Design with copper ground wire in 3/8" to 1-1/4".



Interlocked Design 1-1/2" and up.

UPC	Trade Size	Standard Length Meters / Feet	Min. Inside Bend Diameter (inches)
622620 34202 7	3/8	30 / 100	6
622620 34204 1	3/8	244 / 800	6
622620 34212 6	1/2	30 / 100	7
622620 34213 3	1/2	305 / 1000	7
622620 34222 5	3/4	30 / 100	10
622620 34228 7	3/4	152 / 500	10
622620 34231 7	1	30 / 100	12
622620 34238 6	1	122 / 400	12
622620 34241 6	1-1/4	15 / 50	14
622620 34248 5	1-1/4	76 / 250	14
622620 34251 5	1-1/2	15 / 50	11
622620 34254 6	1-1/2	45 / 150	11
622620 34261 4	2	15 / 50	14
622620 34268 3	2	30 / 100	14

Consult factory for information on larger sizes
Standard colour - grey.



Sealtite® Type UA-CSA additional information

- Constructed of continuous square locked zinc coated steel strip inner core with copper ground wire in sizes from 3/8" to 1-1/4".
- Constructed continuous interlocked zinc coated steel strip inner core on sizes over 1-1/4".
- Uses standard readily available liquid-tight connectors.
- Smooth PVC cover, sunlight resistant, oil resistant (consult factory for oil resistant product).
- Rated from -20° C to + 60° C.
- UL and CSA approved.
- Suitable for Class 1, Div II; Class 2, Div. I & II; Class 3, Div. I & II.
- Suitable for direct burial up to 2".