

METALLIC FITTINGS

SEALTITE® FITTINGS

STAINLESS STEEL AISI-304 PREMIUM NPT FITTINGS



DESCRIPTION

- Stainless 304 corrosion resistance, strength and durability
- IP 66/67 rated when installed with approved conduit and tightened to UL-514B/CSA C22.2 18.3 torque specifications
- Approved for both exposed and concealed locations

SPECIFICATIONS

- AISI-304 with Nickel Plated Brass Ferrule and PA6 clamping ring
- O-ring included
- Colour: silver
- Temp. range: -45° C to +105° C (-49° F to +221° F)
- cULus Approved # E234207

APPLICATIONS


- Metallic and Type B non-metallic flexible conduit
- Premium Stainless 304 for corrosion resistance
- Chemical and food industries

SEALTITE®
FITTINGS

STRAIGHT:



Trade Size	Item ID	Old Item ID	Min. Int. Bore	Dimensions mm				KO Size NPT	Weight kg(lb)/100	Std. Pkg.
				A	B	C	E			
3/8"	814.012.9	SSLT38	10.2	37	13	27	24	1/2"	5.6 (12.3)	10
1/2"	814.016.9	SSLT50	13.9	37	13	30	27	1/2"	6.2 (13.7)	10
3/4"	814.020.9	SSLT75	18.5	40	15	36	36	3/4"	8.9 (19.6)	5
1"	814.026.9	SSLT100	23.8	46	15	46	46	1"	25 (55.1)	5



90 DEGREE:



Trade Size	Item ID	Old Item ID	Min. Int. Bore	Dimensions mm					KO Size NPT	Weight kg(lb)/100	Std. Pkg.
				A	B	C	D	E			
3/8"	814.912.9	SSLT9038	10.2	36	13	27	43	22	1/2"	13.3 (29.3)	10
1/2"	814.916.9	SSLT9050	13.9	36	13	30	43	27	1/2"	14.6 (32.2)	10
3/4"	814.920.9	SSLT9075	18.5	43	15	36	48	33	3/4"	22.0 (48.5)	5
1"	814.926.9	SSLT90100	23.8	48	15	46	59	42	1"	31.7 (69.9)	5

