

SS ULTRA-FLEX SERIES

STAINLESS STEEL FLEX CONNECTORS FOR USE WITH SL/UL-CAP



SPECIFICATIONS

- Type 303 stainless steel (internal ferrule: nickel-plated brass)
- Colour: silver
- Temperature range: -45°C to +105°C (-49°F to +221°F)

DESCRIPTION


- Special ferrule allows connection to either SL conduit
- Excellent for harsh installation
- Excellent protection for small diameter cables or fibre-optics
- Corrosion resistant

SEALTITE® FITTINGS

STRAIGHT:




| SL/UI Size | Item ID | Dimensions mm | | | KO Size NPT | Weight kg(lb)/Pkg | Standard Package |
|------------|---------|---------------|----|----|-------------|-------------------|------------------|
| | | A | B | C | | | |
| 3/8" | SSUI38 | 37 | 13 | 26 | 1/2" | 1.6 (3.5) | 25 |
| 1/2" | SSUI50 | 37 | 13 | 29 | 1/2" | 2.0 (4.4) | 25 |



90 DEGREE:



| SL/UI Size | Item ID | Dimensions mm | | | | KO Size NPT | Weight kg(lb)/Pkg | Standard Package |
|------------|----------|---------------|----|----|----|-------------|-------------------|------------------|
| | | A | B | C | D | | | |
| 3/8" | SSUI9038 | 36 | 13 | 26 | 43 | 1/2" | 1.0 (2.2) | 10 |
| 1/2" | SSUI9050 | 36 | 13 | 29 | 43 | 1/2" | 1.3 (2.9) | 10 |



Special ferrule allows fitting to accept Ultra Flexible SL sizes 3/8" and 1/2". Positive ferrule connection for interconnect to standard NPT applications.

