





### Sealite LT Fittings: Zinc Diecast NPT Fittings

#### Straight:



Trade	Item	Dimensions (mm)			KO Size	Weight	Std.
Size	ID	A	B	C	NPT	Kg(lb)/100	Pkg.
3/8"	LT38	37	13	32	1/2"	6.4 (14.1)	25
1/2"	LT50	37	13	35	1/2"	8.0 (17.6)	25
3/4"	LT75	40	13	44	3/4"	11.0 (24.3)	10
1"	LT100	47	15	48	1"	14.0 (30.9)	5
1-1/4"	LT125	53	16	55	1-1/4"	22.0 (48.5)	5
1-1/2"	LT150	51	16	64	1-1/2"	30.0 (66.1)	2
2"	LT200	53	15	81	2"	40.0 (88.2)	2

#### 90 Degree:



Trade	Item	Dimensions (mm)			KO Size	Weight	Std.
Size	ID	A	B	C	NPT	Kg(lb)/100	Pkg.
3/8"	LT9038	52	13	59	1/2"	10.0 (22.0)	10
1/2"	LT9050	54	13	59	1/2"	13.0 (28.7)	10
3/4"	LT9075	64	13	68	3/4"	16.0 (35.3)	10
1"	LT90100	70	17	92	1"	24.0 (52.9)	5
1-1/4"	LT90125	85	18	99	1-1/4"	40.0 (88.2)	2
1-1/2"	LT90150	89	15	111	1-1/2"	55.0 (121.3)	2
2"	LT90200	104	17	124	2"	75.0 (165.3)	2

#### Sealite LT Series Fittings:

RoHS



- Standard grade fitting.
- Approved for used with metallic and non-metallic conduit.
- Disassembly not required for connection to liquid-tight conduit.

#### SPECIFICATIONS:

- Zinc Die-cast
- Locknut included
- Colour: Silver
- Temperature Range: -18° C to +90° C (0° F to +194° F)
- CSA Approved # LR49636
- UL Approved # E60812

#### APPLICATIONS:

- Metallic and Type B non-metallic Flexible Conduit