

NON-METALLIC SEALTITE® SERIES

STNM FITTINGS

FITTINGS FOR CNP TYPE A CONDUIT (ONLY)




SPECIFICATIONS

- Zinc plated steel, 3-piece
- Colour: silver
- CSA Approved #065178
- UL approved #E11853
- Includes sealing ring, galvanized nut required to connect fitting to box
- Corrosion resistance, strength, durability
- -45°C to 105°C (49°F to 221°F)

DESCRIPTION

- STNM Series liquid tight connectors only approved for use with SEALTITE® CNP flexible conduit




STRAIGHT



Trade Size	Item ID	Dimensions			KO Size NPT	Weight kg(lb)/Pkg	Std. Pkg.
		A	B	C			
3/8"	STNM38	54.76 (2.156)	15.09 (0.594)	29.36 (1.156)	1/2"	2.5 (5.6)	25
1/2"	STNM50	65.89 (2.594)	15.09 (0.594)	33.35 (1.313)	1/2"	3.7 (8.1)	25
3/4"	STNM75	65.89 (2.594)	15.09 (0.594)	41.27 (1.625)	3/4"	5.0 (11.0)	25
1"	STNM100	73.02 (2.875)	18.26 (0.719)	49.23 (1.938)	1"	1.5 (3.2)	5
1-1/4"	STNM125	86.51 (3.406)	19.05 (0.750)	61.11 (2.406)	1-1/4"	2.7 (6.0)	5
1-1/2"	STNM150	87.33 (3.438)	19.05 (0.750)	70.64 (2.781)	1-1/2"	1.4 (3.0)	2
2"	STNM200	100.81 (3.969)	19.05 (0.750)	85.73 (3.375)	2"	1.1 (2.4)	1

All dimensions in mm (inches) unless stated



90 DEGREE



Trade Size	Item ID	Dimensions				KO Size NPT	Weight kg(lb)/Pkg	Std. Pkg.
		A	B	C	D			
3/8"	STNM9038	31.8 (1.25)	15.09 (0.594)	29.36 (1.156)	51.6 (2.03)	1/2"	3.4 (7.5)	25
1/2"	STNM9050	32.5 (1.28)	15.09 (0.594)	33.35 (1.313)	60.5 (2.38)	1/2"	4.3 (9.5)	25
3/4"	STNM9075	36.6 (1.44)	15.09 (0.594)	41.27 (1.625)	63.5 (2.5)	3/4"	2.5 (5.5)	10
1"	STNM90100	44.5 (1.75)	18.26 (0.719)	49.23 (1.938)	69.9 (2.75)	1"	1.9 (4.1)	5
1-1/4"	STNM90125	50.0 (1.97)	19.05 (0.750)	61.11 (2.406)	88.1 (3.47)	1-1/4"	3.5 (7.7)	5
1-1/2"	STNM90150	57.2 (2.25)	19.05 (0.750)	70.64 (2.781)	91.2 (3.59)	1-1/2"	1.8 (4.0)	2
2"	STNM90200	64.3 (2.53)	19.05 (0.750)	85.73 (3.375)	112.0 (4.41)	2"	1.4 (3.1)	1

All dimensions in mm (inches) unless stated

NON-METALLIC SEALTITE®