

SPECIALTY SERIES

SEALTITE® AS ANTI-STATIC FLEXIBLE CONDUIT



DESCRIPTION

- Robust conduit for use in hazardous areas where a risk of explosion exists
- Conduit cover provides surface resistance of $<10^9$ Ohm, thus preventing electrostatic charge from accumulating on the surface of the conduit cover as well as sparks in the case of discharge by contact
- Suitable for outdoor and burial installations

SPECIFICATIONS

- Galvanized steel core with thick smooth anti-static PVC cover
- Colour: black
- Temp. range: -25°C to $+70^{\circ}\text{C}$ (-13°F to $+158^{\circ}\text{F}$), intermittent up to $+90^{\circ}\text{C}$ ($+194^{\circ}\text{F}$)
- UV (sunlight) resistant, lead free

APPLICATIONS

- Suitable for outside installation
- Hazardous locations in conjunction with ATEX fittings in order to avoid sparks

METALLIC
SEALTITE®



Square-Locked Design from 3/8" - 1-1/4"



Interlocked Design 1-1/2" - 2"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter Min	Bend Radius		Weight kg/m (lbs/cft)
					Static	Dynamic	
3/8" (12)	350.012.1	30 (100)	12.6 (0.496)	17.8 (0.701)	60 (2.4)	85 (3.3)	0.30 (20.13)
1/2" (16)	350.016.1	30 (100)	16.0 (0.630)	21.1 (0.831)	75 (3.0)	110 (4.3)	0.40 (26.84)
3/4" (21)	350.020.1	30 (100)	21.0 (0.827)	26.4 (1.039)	90 (3.5)	140 (5.5)	0.55 (36.90)
1" (27)	350.026.1	30 (100)	26.5 (1.043)	33.1 (1.303)	120 (4.7)	170 (6.7)	0.75 (50.32)
1-1/4" (35)	350.035.1	15 (50)	35.1 (1.381)	41.8 (1.646)	150 (5.9)	215 (8.5)	1.00 (67.09)
1-1/2" (41)	350.040.1	15 (50)	40.3 (1.589)	47.8 (1.882)	200 (7.9)	250 (9.8)	1.55 (104.00)
2" (53)	350.050.1	15 (50)	51.6 (2.031)	59.9 (2.358)	350 (13.8)	300 (11.8)	2.15 (144.26)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 47-50