

# SEALTITE® SERIES

## SEALTITE® CSA STANDARD FLEXIBLE CONDUIT



### DESCRIPTION:

- Flexible metal core liquid-tight conduit
- Available by special order in other colours and custom cut lengths
- Sequentially meter marked for easy cutting and stock control
- Uses standard liquid-tight connectors for easy installation
- Available in custom cut lengths
- New - Approved for direct burial

### SPECIFICATIONS:

- Galvanized steel core with liquid-tight PVC jacket
- Colour: black
- Temp. range: -20°C to +75°C (-4°F to + 167°F)
- UV (sunlight) resistant
- Corrosion resistant
- Direct Burial rated
- FT-4 rated
- Sequentially meter marked
- CSA Approved #17419

### APPLICATIONS:

- Standard industrial and commercial applications
- Motor hookup

METALLIC  
SEALTITE®



Square-Locked Design 3/8" - 2"



Interlocked Design 2-1/2" - 4"



Trade Size	Item ID	Std. Pkg. metres	Inside Diameter		Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
			Min	Max	Min	Max		
3/8" (12)	10041	30	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	51 (2.0)	0.35 (24)	
	10044	300						
1/2" (16)	10061	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	76 (3.0)	0.42 (28)	
	10063	150						
	10064	300						
3/4" (21)	10071	30	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	102 (4.0)	0.55 (37)	
	10073	150						
	10074	300						
1" (27)	10081	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	127 (5.0)	0.80 (54)	
	10083	150						
1-1/4" (35)	10090	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	159 (6.3)	1.13 (76)	
	10091	75						
1-1/2" (41)	10100	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	191 (7.5)	1.45 (97)	
	10101	45						
2" (53)	10111	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	254 (10.0)	1.67 (112)	
	10113	30						
2-1/2" (63)	34075	8	62.99 (2.480)	72.10 (2.840)	73.00 (2.875)	318 (9.5)	2.88 (182)	
	34074	30						
3" (78)	34085	8	77.98 (3.070)	87.90 (3.460)	88.90 (3.500)	381 (15.0)	4.00 (255)	
	34084	30						
4" (103)	34095	8	101.60 (4.000)	113.30 (4.460)	114.30 (4.500)	508 (17.0)	6.00 (362)	
	34094	30						

All dimensions in mm (inches) unless stated



PAGE 33-38



PAGE 36



PAGE 41

Made in Canada from 100% North American materials