

# SEALTITE® SERIES

## SEALTITE® EFL ALUMINUM CORE FLEXIBLE CONDUIT



### DESCRIPTION

- Flexible aluminum core liquid-tight conduit
- Designed for applications where weight is a major concern, such as the transportation industry
- Lightweight
- Uses standard liquid-tight connectors for easy installation

### SPECIFICATIONS

- Aluminum core with liquid-tight PVC jacket
- Colour: grey
- Temp. range: -20°C to +60°C (-4°F to + 140°F)
- UV (sunlight) resistant
- Corrosion resistant

### APPLICATIONS

- Applications where weight is a concern
- Rail cars and locomotives
- Transport trucks/trailers
- Applications where no approvals are required



Square-Locked Design with cord packing 3/8" - 1-1/4"

Interlocked Design 1-1/2" - 4"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
3/8" (12)	38002	30 (100)	12.32 (0.485)	17.53 (0.690)	18.03 (0.710)	51 (2.0)	0.21 (14)
1/2" (16)	38012	30 (100)	15.75 (0.620)	20.83 (0.820)	21.34 (0.840)	64 (2.5)	0.24 (16)
3/4" (21)	38022	30 (100)	20.70 (0.815)	26.16 (1.030)	26.67 (1.050)	76 (3.0)	0.28 (19)
1" (27)	38031	30 (100)	26.16 (1.030)	32.77 (1.290)	33.40 (1.315)	102 (4.0)	0.48 (32)
1-1/4" (35)	38041	15 (50)	34.80 (1.370)	41.53 (1.635)	42.16 (1.660)	115 (4.5)	0.63 (42)
1-1/2" (41)	38051	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	140 (5.5)	0.86 (58)
2" (53)	38061	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	178 (7.0)	1.16 (78)
2-1/2" (63)	38071	15 (50)	62.99 (2.480)	72.10 (2.840)	73.00 (2.875)	318 (9.5)	1.53 (103)
3" (78)	38081	7.6 (25)	77.98 (3.070)	87.90 (3.460)	88.90 (3.500)	381 (15.0)	1.83 (123)
4" (103)	38091	7.6 (25)	101.60 (4.000)	113.30 (4.460)	114.30 (4.500)	508 (17.0)	2.92 (196)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 33-38



PAGE 36