

# SEALTITE® SERIES

## SEALTITE® EFST EXTRA FLEXIBLE CONDUIT



### SPECIFICATIONS:

- Galvanized steel core with liquid-tight PVC jacket
- Colour: 1/4" to 5/16" black, 3/8" to 6" grey
- Temp. range: -20°C to +60°C (-4°F to + 140°F)
- UV (sunlight) resistant
- Corrosion resistant

### APPLICATIONS:

- Applications where very small ID liquid-tight is required (ie: 1/4")
- Applications where no approvals are required

### DESCRIPTION:

- Flexible metal core liquid-tight conduit
- Designed for applications where no approvals are required
- Also available in black by special order
- Uses standard liquid-tight connectors for easy installation
- Available in custom cut lengths



Square-Locked Design with cord packing 5/16" - 1-1/4"

Interlocked Design 1/4" and 1-1/2" - 4"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter		Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
			Min	Max	Min	Max		
1/4"	35983	30 (100)	6.22 (0.245)	11.30 (0.445)	11.68 (0.460)	45 (1.8)	0.21 (14)	
	35981	152 (500)						
5/16" (10)	35993	30 (100)	9.91 (0.390)	14.22 (0.560)	14.61 (0.575)	51 (2.0)	0.22 (15)	
	35991	152 (500)						
3/8" (12)	36202	30 (100)	12.32 (0.485)	17.53 (0.690)	18.03 (0.710)	51 (2.0)	0.31 (21)	
1/2" (16)	36212	30 (100)	15.75 (0.620)	20.83 (0.820)	21.34 (0.840)	64 (2.5)	0.37 (25)	
3/4" (21)	36222	30 (100)	20.70 (0.815)	26.16 (1.030)	26.67 (1.050)	76 (3.0)	0.58 (39)	
1" (27)	36231	30 (100)	26.16 (1.030)	32.77 (1.290)	33.40 (1.315)	102 (4.0)	0.76 (51)	
1-1/4" (35)	36241	15 (50)	34.80 (1.370)	41.53 (1.635)	42.16 (1.660)	115 (4.5)	0.98 (66)	
1-1/2" (41)	36251	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	140 (5.5)	1.55 (104)	
2" (53)	36261	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	178 (7.0)	2.02 (136)	
2-1/2"	34281	7.6 (25)	62.99 (2.480)	72.14 (2.840)	73.03 (2.875)	241 (9.5)	2.71 (182)	
3"	34201	7.6 (25)	77.98 (3.070)	87.88 (3.460)	88.90 (3.500)	381 (15.0)	3.79 (255)	
3-1/2"	34291	7.6 (25)	88.90 (3.500)	100.58 (3.960)	101.60 (4.000)	407 (16.0)	4.67 (314)	
4"	36351	7.6 (25)	101.60 (4.000)	113.28 (4.460)	114.30 (4.500)	432 (17.0)	5.40 (363)	
5"	36351	7.6 (25)	126.37 (4.975)	139.83 (5.505)	141.35 (5.565)	559 (22.0)	7.94 (534)	
6"	36361	7.6 (25)	152.78 (6.015)	166.75 (6.565)	168.28 (6.625)	762 (30.0)	9.91 (666)	

All dimensions in mm (inches) unless stated



PAGE 33-38



PAGE 36



PAGE 41

METALLIC SEALTITE®