

# SPECIALTY SERIES

## SEALTITE® FG FOOD GRADE FLEXIBLE CONDUIT



### DESCRIPTION

- Constructed with thermoplastic PVC jacket over galvanized steel inner core
- PVC jacket specially formulated for food and beverage applications per FDA CFR 21 and NSF 51 requirements
- Jacket is easily cleaned and does not promote bacteria growth

### SPECIFICATIONS

- Galvanized steel core with thick smooth PVC cover
- Colour: white
- Temp. range: -20°C to +60°C (-4°F to +140°F)
- NSF Certified to NSF / ANSI 169 for special purpose food equipment or devices

### APPLICATIONS

- Suitable for food equipment or devices
- Food equipment manufacturers
- Meat packing or poultry facilities
- Pharmaceutical facilities



Square-Locked Design with cord packing from 3/16" - 1-1/4"



Interlocked Design 1-1/2" - 4"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
3/8" (12)	35502	30 (100)	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	51 (2.0)	0.31 (21)
1/2" (16)	35512	30 (100)	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	64 (2.5)	0.37 (25)
3/4" (21)	35522	30 (100)	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	76 (3.0)	0.58 (39)
1" (27)	35531	30 (100)	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	102 (4.0)	0.76 (51)
1-1/4" (35)	35541	15 (50)	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	115 (4.5)	0.98 (66)
1-1/2" (41)	35551	15 (50)	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	140 (5.5)	1.55 (104)
2" (53)	35561	15 (50)	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	176 (7.0)	2.02 (136)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 33-38



PAGE 36