

HIGH-TEMP SERIES

SEALTITE® HTC HIGH TEMPERATURE FLEXIBLE CONDUIT



DESCRIPTION

- Flexible metal core liquid-tight conduit
- Designed for applications where high temperature is required
- Also available by special order in other colours (consult factory)
- Sequentially meter marked for easy cutting and stock control
- Uses standard liquid-tight connectors for easy installation
- Available in custom cut lengths

SPECIFICATIONS

- Galvanized steel core with liquid-tight PVC jacket
- Colour: black
- Temp. range: -20°C to +105°C (-4°F to + 221°F)
- UV (sunlight) resistant
- Corrosion resistant
- Sequentially meter marked
- CSA Approved #17419

APPLICATIONS

- Applications for high temperature
- Steel and petrochemical industries



Square-Locked Design
3/8" - 2"



Trade Size	Item ID	Std. Pkg. metres	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
3/8" (12)	14041	30	12.29 (0.484)	17.5 (0.690)	18.00 (0.710)	51 (2.0)	0.33 (22)
1/2" (16)	14061	30	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	76 (3.0)	0.40 (27)
	14062	150					
	14063	300					
3/4" (21)	14071	30	20.83 (0.820)	26.17 (1.030)	26.67 (1.050)	102 (4.0)	0.53 (36)
	14072	150					
	14072	300					
1" (27)	14081	30	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	127 (5.0)	0.73 (49)
	14083	150					
1-1/4" (35)	14090	15	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	159 (6.7)	1.07 (72)
1-1/2" (41)	14100	15	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	191 (7.5)	1.33 (89)
2" (53)	14112	15	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	254 (10.0)	1.67 (112)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 33-38



PAGE 36



PAGE 41

Made in Canada from 100% North American materials