

SEALTITE® SERIES

SEALTITE® MTC MACHINE TOOL EXTRA FLEXIBLE CONDUIT



SPECIFICATIONS

- Galvanized steel core with liquid-tight PVC jacket
- Colour: black
- Temp. range: -20°C to +60°C (-4°F to + 140°F)
- UV (sunlight) resistant
- Corrosion resistant
- Tight bend radius

APPLICATIONS

- High flexibility
- Machine tool industry

DESCRIPTION

- Flexible metal core liquid-tight conduit
- Designed for Machine Tool industry for high flexibility
- Very tight bend radius makes wiring machine tools easier
- Uses standard liquid-tight connectors for easy installation



Square-Locked Design
3/8" - 2"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
3/8" (12)	38302	30 (100)	12.29 (0.484)	17.25 (0.679)	17.88 (0.704)	38 (1.5)	0.24 (16)
	38304	244 (800)					
1/2" (16)	38312	30 (100)	15.80 (0.622)	20.78 (0.818)	21.41 (0.843)	51 (2.0)	0.30 (20)
	38314	152 (500)					
3/4" (21)	38322	30 (100)	20.83 (0.820)	25.63 (1.009)	26.26 (1.034)	64 (2.5)	0.36 (24)
	38328	152 (500)					
1" (27)	38331	30 (100)	26.44 (1.041)	31.19 (1.228)	31.95 (1.258)	76 (3.0)	0.45 (30)
	38338	122 (400)					
1-1/4" (35)	38341	15 (50)	35.05 (1.380)	39.75 (1.565)	40.51 (1.595)	89 (3.5)	0.60 (40)
	38348	76 (250)					
1-1/2" (41)	38351	15 (50)	40.01 (1.575)	46.48 (1.830)	47.24 (1.860)	102 (4.0)	1.04 (70)
	38354	46 (150)					
2" (53)	38361	15 (50)	51.31 (2.020)	57.66 (2.270)	58.42 (2.300)	127 (5.0)	1.29 (87)
	38638	30 (100)					

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 33-38



PAGE 36



PAGE 41