

NON-METALLIC SEALTITE® SERIES

SEALTITE® NMEF (TYPE B) NON-METALLIC FLEXIBLE TUBING



DESCRIPTION

- Non-metallic Type B liquid-tight tubing
- Designed for OEM and industrial applications
- Uses special non-metallic connectors for easy installation. Can also be used with standard liquid-tight connector
- Available in custom cut lengths

SPECIFICATIONS

- Co-extruded PVC conduit
- Extra flexible
- Colour: black
- Temperature range: -18°C to 80°C (0°F to +176°F)
- UV (sunlight) resistant
- Oil resistant
- CSA Approved

APPLICATIONS

- OEM machine building
- Industrial applications where tight bend radius is required



Co-extruded special with smooth inner wall



Trade Size	Part Numbers	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
					Min	Max		
1/4" (10)	362.010.0*	N/A	30 (100)	9.78 (0.385)	14.22 (0.560)	14.61 (0.575)	20 (0.8)	0.12 (8)
3/8" (12)	362.012.0	39802	30 (100)	12.29 (0.484)	17.53 (0.690)	18.03 (0.710)	20 (0.8)	0.13 (9)
1/2" (16)	362.016.0	39812	30 (100)	15.80 (0.622)	20.83 (0.820)	21.34 (0.840)	23 (0.9)	0.17 (11)
3/4" (21)	362.020.0	39822	30 (100)	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	25 (1.0)	0.20 (13)
1" (27)	362.026.0	39831	30 (100)	26.44 (1.041)	32.77 (1.290)	33.40 (1.315)	36 (1.4)	0.30 (20)
1-1/4" (35)	362.035.0	39841	30 (100)	35.05 (1.380)	41.40 (1.630)	42.16 (1.660)	43 (1.7)	0.33 (22)
1-1/2" (41)	362.040.0	39853	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	51 (2.0)	0.40 (27)
2" (53)	362.050.0	39861	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	203 (8.0)	0.67 (45)

All dimensions in mm (inches) unless stated
*1/4" CSA pending approval

FITTINGS FINDER



PAGE 56