

# NON-METALLIC SEALTITE® SERIES

## SEALTITE® NMUA (TYPE B) NON-METALLIC FLEXIBLE CONDUIT



### DESCRIPTION

- Non-metallic Type B liquid-tight conduit
- Designed for standard commercial and industrial applications
- Approved in US (per NEC) for direct burial applications
- Also available by special order in other colours (consult factory)
- Uses special non-metallic connectors for easy installation. Can also be used with standard liquid-tight connector
- Available in custom cut lengths

### SPECIFICATIONS

- Co-extruded PVC conduit
- Colour: grey
- Temp. range: Dry: -18°C to +80°C (0°F to +176°F)  
Wet: 60°C (+140°F) Oil 70°C (158°F)
- UV (sunlight) resistant
- Oil resistant
- CSA Approved #20817
- UL Approved #E211327

### APPLICATIONS

- HVAC industry
- Commercial and industrial applications requiring UL & CSA approvals



Rigid PVC Reinforced 3/8" through 2"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
3/8" (12)	39302	30 (100)	12.29 (0.484)	17.53 (0.690)	18.03 (0.710)	51 (2.0)	0.17 (11)
1/2" (16)	39312	30 (100)	15.80 (0.622)	20.83 (0.820)	21.34 (0.840)	83 (3.3)	0.23 (15)
	39313	150 (500)					
	39314	300 (1000)					
3/4" (21)	39322	30 (100)	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	216 (4.5)	0.30 (20)
	39323	150 (500)					
1" (27)	39331	30 (100)	26.44 (1.041)	32.77 (1.290)	33.40 (1.315)	108 (6.5)	0.40 (27)
1-1/4" (35)	39341	15 (50)	35.05 (1.380)	41.40 (1.630)	42.16 (1.660)	203 (8.0)	0.53 (36)
1-1/2" (41)	39353	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	229 (9.0)	0.67 (45)
2" (53)	39361	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	282 (11.1)	1.00 (67)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 56