

# SEALTITE® SERIES

## SEALTITE® OR OIL-RESISTANT FLEXIBLE CONDUIT



### DESCRIPTION:

- Flexible metal core liquid-tight conduit
- Designed for applications that need superior resistance to petroleum, synthetic oils and chemical degradation
- Uses standard liquid-tight connectors for easy installation

### SPECIFICATIONS

- Galvanized steel core with liquid-tight PVC jacket
- Colour: black
- Temp. range: -23°C to +105°C (-9°F to + 221°F)
- UV (sunlight) resistant
- Corrosion resistant
- Extra oil resistant

### APPLICATIONS

- Extreme resistance to oil
- Petrochemical and steel industries
- Applications where no approvals are required

METALLIC  
SEALTITE®



Square-Locked Design with cord packing 3/8" - 1-1/4"

Interlocked Design 1-1/2" - 2"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
3/8" (12)	36602	30 (100)	12.32 (0.485)	17.53 (0.690)	18.03 (0.710)	51 (2.0)	0.31 (21)
1/2" (16)	36612	30 (100)	15.75 (0.620)	20.83 (0.820)	21.34 (0.840)	64 (2.5)	0.37 (25)
3/4" (21)	36622	30 (100)	20.70 (0.815)	26.16 (1.030)	26.67 (1.050)	76 (3.0)	0.58 (39)
1" (27)	36631	30 (100)	26.16 (1.030)	32.77 (1.290)	33.40 (1.315)	102 (4.0)	0.76 (51)
1-1/4" (35)	36641	15 (50)	34.80 (1.370)	41.53 (1.635)	42.16 (1.660)	115 (4.5)	0.98 (66)
1-1/2" (41)	36651	15 (50)	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	140 (5.5)	1.55 (104)
2" (53)	36661	15 (50)	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	178 (7.0)	2.02 (136)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 33-38



PAGE 36



PAGE 41