

HIGH-TEMP SERIES

SEALTITE® XTHF LOW TEMPERATURE FLEXIBLE CONDUIT



DESCRIPTION

- Flexible metal core liquid-tight conduit
- Uses standard liquid-tight connectors for easy installation
- Rated for temperature range of -70°C to +200°C (-94°F to +392°F) and incursions up to 260°C (500°F) Can be used in applications that do not require approvals
- Exceptional crush and corrosion resistance
- Durable, sunlight resistant, flame retardant, low smoke and zero halogen silicone jacket that resists heat, oil and corrosive chemical breakdown.

SPECIFICATIONS

- Hot dipped zinc galvanized steel core with silicone jacket
- Colour: grey
- Temp. range: -70°C to +200°C (-94°F to +392°F)
- UV (sunlight) resistant. flame retardant, halogen free

APPLICATIONS

- Designed for the most extreme temperature applications
- Silicone jacket has superior resistance to chemical breakdown



Square-Locked Design with integral bonding wire 1/2" - 1"



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
1/2" (16)	34712	30 (100)	15.80 (0.622)	20.88 (0.822)	21.34 (0.840)	45 (3.5)	0.45 (30)
3/4" (21)	34722	30 (100)	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	64 (5.0)	0.65 (43)
1" (27)	34731	30 (100)	26.44 (1.041)	32.77 (1.290)	33.40 (1.315)	76 (6.0)	1.05 (71)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 33-38



PAGE 36