

ULTRA-FLEX SERIES

STEEL FLEX DE-710 STANDARD FLEXIBLE CONDUIT



DESCRIPTION

- Ultra flexible galvanized steel conduit
- Designed for OEM applications in the office furniture and medical industries
- UL Recognized to DXUZ2.
- Also available in an OVAL version (consult factory)
- Available in custom cut lengths

SPECIFICATIONS

- Galvanized steel square-lock non-jacketed conduit
- Zinc coated steel provides superior corrosion resistance
- Temperature: +450°C (+842°F) max.
- Exceptional flexibility for tight "U" bend radius
- UL Recognized: #E-39679, DXUZ2
- CSA Acceptable. CSA Report No. LO 4000-4158

APPLICATIONS

- OEM applications in office furniture and medical markets



Square-Locked Design

DE-710:



Actual ID Size	Item ID	Std. Pkg. metres	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
5/16"	452100	Available in Random Lengths	7.95 (0.313)	11.58 (0.456)	12.22 (0.481)	32 (1.3)	0.164 (11)
3/8"	452105		9.53 (0.375)	13.18 (0.519)	13.82 (0.544)	32 (1.3)	0.18 (12)
7/16"	452110		11.13 (0.438)	14.76 (0.581)	15.39 (0.606)	38 (1.5)	0.198 (13)
1/2"	452115		12.70 (0.500)	16.36 (0.644)	16.99 (0.669)	38 (1.5)	0.225 (15)
* 9/16"	452120		14.30 (0.563)	17.98 (0.708)	18.57 (0.731)	38 (1.5)	0.286 (19)
5/8"	452125		15.87 (0.625)	18.75 (0.738)	19.38 (0.763)	45 (1.8)	0.255 (17)
3/4"	452130		19.05 (0.750)	21.34 (0.840)	22.10 (0.870)	51 (2.0)	0.295 (20)

All dimensions in mm (inches) unless stated

* Old Profile