

ANA-QUICK® ACCESSORIES

SUPPORT WITH LID



SPECIFICATIONS:

- Made of specially modified polyamide (PA6)
- Free of halogen, phosphorus and cadmium
- Self-extinguishing
- Shock-resistant
- With integrated lid
- Temp. range: -40°C to +105°C (150°C short term)

DESCRIPTION:

Supports with integrated lid for securing sections of corrugated conduits between the various parts of the electrical installation. With conduit entry guide.

Specially designed for demanding securing situations, (e.g. on ceilings)

SUPPORTS WITH INTEGRATED LIDS

Size NW	Item ID	Dimensions mm (inches)				Metric m	Std. Pkg.
		A	B	C	H		
7	ARNS-07NB	22 (0.866)	17 (0.669)	20 (0.787)	13 (0.512)	M4	100
10	ARNS-10NB	25 (0.984)	22 (0.866)	20 (0.787)	13 (0.512)	M5	100
12	ARNS-12NB	27 (1.063)	25 (0.984)	20 (0.787)	13 (0.512)	M5	100
17	ARNS-17NB	33 (1.299)	31 (1.221)	20 (0.787)	19 (0.748)	M5	100
23	ARNS-23NB	42 (1.654)	40 (1.575)	20 (0.787)	23 (0.906)	M6	50
29	ARNS-29NB	47 (1.850)	46 (1.811)	20 (0.787)	26 (1.024)	M6	30
36	ARNS-36NB	56 (2.205)	56 (2.205)	20 (0.787)	31 (1.221)	M6	20
48	ARNS-48NB	70 (2.756)	70 (2.756)	20 (0.787)	39 (1.535)	M6	10

