

FIRETECH

FIRETECH SLEEVE



DESCRIPTION

- Solid braided glass fibre sleeving, with thick silicone cover
- Superior short-term flame protection and excellent temperature reduction
- Resistant to hydraulic fluids, lubricating oils and fuels
- Protects against molten splash, occasional flames, heat radiation, energy loss in piping and hoses
- Protects workers from burns

FIRETECH SLEEVE:

Item ID	Inside Diameter	Std. Pkg. ft	Weight kg/m (lbs/cft)
FTS-4-1	1/4"	100	3.20 (7.1)
FTS-4-5	1/4"	50	1.60 (3.5)
FTS-5-1	5/16"	100	3.60 (7.9)
FTS-5-5	5/16"	50	1.80 (4.0)
FTS-6-1	3/8"	100	4.50 (9.9)
FTS-6-5	3/8"	50	2.25 (5.0)
FTS-7-1	7/16"	100	5.00 (11.0)
FTS-7-5	7/16"	50	2.50 (5.5)
FTS-8-1	1/2"	100	5.90 (13.0)
FTS-8-5	1/2"	50	2.95 (6.5)
FTS-10-1	5/8"	100	6.40 (14.1)
FTS-10-5	5/8"	50	3.20 (7.1)
FTS-12-1	3/4"	100	7.70 (17.0)
FTS-12-5	3/4"	50	3.85 (8.5)
FTS-12-9	3/4"	1	0.07 (0.2)
FTS-14-1	7/8"	100	8.19 (18.1)
FTS-14-5	7/8"	50	4.09 (9.0)
FTS-16-1	1"	100	9.50 (20.9)
FTS-16-5	1"	50	4.75 (10.5)
FTS-18-1	1-1/8"	100	10.00 (22.1)
FTS-18-5	1-1/8"	50	5.00 (11.0)

SPECIFICATIONS

- Silicone over braided glass fibre sleeve
- cURus Recognized
- Colour: orange
- Temp. range:
 - +260°C (500°F) continuous,
 - +1090°C (2000°F) for 15-20 min.
 - +1650°C (3000°F) for 15-30 sec.

APPLICATIONS

- Extreme duty applications
- Extreme heat or flame

Item ID	Inside Diameter	Std. Pkg. ft	Weight kg/m (lbs/cft)
FTS-20-1	1-1/4"	100	11.80 (26.0)
FTS-20-5	1-1/4"	50	5.90 (13.0)
FTS-22-1	1-3/8"	100	13.60 (30.0)
FTS-22-5	1-3/8"	50	6.80 (15.0)
FTS-24-1	1-1/2"	100	15.50 (34.2)
FTS-24-5	1-1/2"	50	7.75 (17.1)
FTS-26-1	1-5/8"	100	15.90 (35.1)
FTS-26-5	1-5/8"	50	7.95 (17.5)
FTS-28-1	1-3/4"	100	16.39 (36.2)
FTS-28-5	1-3/4"	50	8.19 (18.1)
FTS-32-1	2"	100	18.20 (40.1)
FTS-32-5	2"	50	9.10 (20.1)
FTS-36-1	2-1/4"	100	19.50 (43.0)
FTS-36-5	2-1/4"	50	9.75 (21.5)
FTS-40-1	2-1/2"	100	20.90 (46.1)
FTS-40-5	2-1/2"	50	10.45 (23.0)
FTS-44-1	2-3/4"	100	23.20 (51.2)
FTS-44-5	2-3/4"	50	11.60 (25.6)
FTS-48-1	3"	100	26.40 (58.2)
FTS-48-5	3"	50	13.20 (29.1)
FTS-52-1	3-1/4"	100	31.40 (69.2)
FTS-52-5	3-1/4"	50	15.70 (34.6)
FTS-56-1	3-1/2"	100	32.70 (72.1)
FTS-56-5	3-1/2"	50	16.35 (36.1)
FTS-60-1	3-3/4"	100	33.60 (74.1)
FTS-60-5	3-3/4"	50	16.80 (37.0)
FTS-64-1	4"	100	35.00 (77.2)
FTS-64-5	4"	50	17.50 (38.6)

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 61

